

DANOCOAT 250

Pure polyurea membrane with high mechanical and chemical strength and high elasticity.



EPD[®]



EPD S-P-03356



ETE 17/ 0401

Pure polyurea membrane with high mechanical and chemical strength and high elasticity.

Presentation

- Colour: White
- Product code: 750783

Technical Data

Concept	Value	Standard
Additional Technical Data		
Concept	Value	Standard
Potable water compatibility according to RD 3/2023	Apto	UNE-EN 12873-2 Parte 2

Scope

- Waterproofing of balconies and terraces.
- Roof waterproofing.

Advantages & Benefits

- High resistance to root penetration.
- Suitable for vehicular and pedestrian traffic.

Support

- Concrete, ceramics, steel, sheet metal, aluminum, aged PVC (Contact the Technical Department for a system analysis), bituminous sheets, polyurethane foam density >50 kg/m³, wood, etc.

Substrate preparation

- Any previous coating will need to be removed.
- The substrate shall be cohesive, without loose particles, with a regular surface texture.
- The substrates must be clean and sound, free of grease, paint or other substances that would prevent proper adhesion.

Instruction for Use

- Before applying the product, check that the application surface is dry, clean and free of solid debris and irregularities.
- Protect yourself adequately for handling the components with appropriate gloves and mask. See safety data sheet.
- Mix the two components in the plastic container to a uniform mass.
- Apply to cracks and joints first. We recommend using 4×4 mm fibreglass reinforcement (PX160 mesh).
- Use a trowel/roller to apply the first coat and place in fresh PX160 Mesh reinforcement also in the corners.
- Apply the remaining coats crosswise to the previous coat for best result (see Drying Time).

Cleaning of Work Tools

- If the product is fresh, with water
- If the product is dry, scraping

Safety and hygiene

- Consult the safety data sheet.

Notice

- The information contained in this document and any other advice provided, are given in good faith, based on DANOSA's current knowledge and experience when products are properly stored, handled and applied, in normal situations and in accordance with the recommendations of DANOSA. The information applies only to the application (s) and the product (s) to which reference is expressly made. In case of changes in the parameters of the application, or in case of a different application, consult the DANOSA Technical Service before using the DANOSA products. The information contained herein does not exonerate the responsibility of the building agents to test the products for the application and intended use, as well as their correct application in accordance with current legal regulations. The product images used in our communications are indicative and may differ slightly in color and aesthetic appearance in relation to the final product. Orders are accepted in

accordance with the terms of our current General Sales Conditions.DANOSA reserves the right to modify, without prior notice, the data reflected in this documentation.Website: **www.danosa.com** E-mail: **info@danosa.com** Telephone: **+34 949 88 82 10**