Ancillaries

GLUEDAN ACUSTIC

Contact adhesive for acoustic insulation

Contact adhesive for fixing the entire range of acoustic insulation products on vertical and horizontal partitions. Easy to apply with a roller, odorless, solvent-free, fast-drying, and long-lasting.

Scope

- Specifically developed for bonding foams to wood, plasterboard panels, fabrics, polystyrene, etc., in the acoustic insulation of walls, floors, and more.

Advantages & Benefits

- Fast drying.
- High initial cohesion.
- High final bond strength and high performance.
- Great versatility, providing excellent adhesion on a wide variety of substrates.
- Fast setting time.

Substrate preparation

- Clean of impurities and dust and guarantee the stability of the support element prior to application.
- Check that the surface is dry.

Instruction for Use

Bilateral application with a roller or spatula, applying a continuous layer on each surface to be bonded.

Optimal coverage: 500
- 650 g/m².

Drying time: 15 minutes (may vary depending on hygrothermal conditions).

Indications and Important Recommendations

- Recommended temperature for application > 10ºC.

Handling, storage and preservation

- Shelf life of 12 months.
- Store protected from the elements and at a temperature between 5 and 35°C.

Notice

- The information contained in this document and any other advice provided, are given in good faith, based on DANOSA's current knowledge and experience when products are properly stored, handled and applied, in normal situations and in accordance with the recommendations of DANOSA. The information applies only to the application (s) and the product (s) to which reference is expressly made. In case of changes in the parameters of the application, or in case of a different application, consult the DANOSA Technical Service before using the DANOSA products. The information contained herein does not exonerate the responsibility of the building agents to test the products for the application and intended use, as well as their correct application in accordance with current legal regulations. The product images used in our communications are indicative and may differ slightly in color and aesthetic appearance in relation to the final product.Orders are accepted in accordance with the terms of our current General Sales Conditions.DANOSA reserves the right to modify, without prior notice, the data reflected in this documentation.Website: **www.danosa.com** E-mail: **info@danosa.com** Telephone: **+34 949 88 82 10**