

TUBODAN

Complementary drainage pipe for DANODREN H products



High-density polyethylene (HDPE) corrugated pipe, highly flexible and perforated around its entire perimeter.

Presentation

- Length (cm): 5000
- Product code: 315005

Technical Data

Concept	Value	Standard
---------	-------	----------

Scope

- Sports fields.
- Channelling water seeping through walls.
- Gardening, to control ground water and sanitation of crop fields.
- Civil Works, on motorways, roads, railways, etc.
- Perimeters of building basement walls and retaining walls. Foundations and slabs.
- Urbanisations, on roads and urban roads.

Advantages & Benefits

- Facilitates the collection and channelling of water, both from direct filtration and water deposited on the support base of the pipe.
- It favours the channelling of water without clogging.
- Great elasticity.
- Very easy to assemble thanks to flexibility and incorporated connecting sleeves.
- They allow it to adapt to the terrain and the layout of the installation and considerably reduce the risk of breakage.

- The holes are protected by a "bridge eye".
- 360° perforated
- Allows groundwater to be easily controlled, thanks to its drainage and channelling capacity.
- Its high infiltration capacity allows the entire duct section to be considered as a useful section to obtain the flow rate.

Indications and Important Recommendations

- It is advisable to lay the drainage pipe on walls as the protection with the drainage sheet is being extended.
- This product may form part of a waterproofing system, so all the documents referred to in the Danosa Solutions Manual must be taken into account, as well as all the regulations and legislation that must be complied with in this respect.
- Appropriate precautions shall be taken so as not to pierce the waterproofing during the laying of the product.
- NOTE: For more information on the Danosa systems in which this product is used, please see the document "Waterproofing Solutions".

Handling, storage and preservation

- The product must be stored in a dry place protected from rain, sun, heat and low temperatures.
- The product must be stored horizontally.
- The product will be used on a first-come, first-served basis.
- This product is not toxic.
- Easy to cut to adapt the dimensions to the work.
- Danosa recommends consulting the safety data sheet for this product, which is permanently available at danosa.com, Knowledge Portal, or it can be requested from our Technical Department.
- In all cases, the Occupational Safety and Hygiene standards, as well as the standards of good construction practice, must be taken into account.
- For further information, please contact our Technical Department.

Notice

- The information contained in this document and any other advice provided, are given in good faith, based on DANOSA's current knowledge and experience when products are properly stored, handled and applied, in normal situations and in accordance with the recommendations of DANOSA. The information applies only to the application (s) and the product (s) to which reference is expressly made. In case of changes in the parameters of the application, or in case of a different application, consult the DANOSA Technical Service before using the DANOSA products. The information contained herein does not exonerate the responsibility of the building agents to test the products for the application and intended use, as well as their correct application in accordance with current legal regulations. The product images used in our communications are indicative and may differ slightly in color and aesthetic appearance in relation to the final product. Orders are accepted in accordance with the terms of our current General Sales Conditions. DANOSA reserves the right to modify, without prior notice, the data reflected in this documentation. Website: **www.danosa.com** E-mail: **info@danosa.com** Telephone: **+34 949 88 82 10**