

Disclaimer: Drawings produced by DANOSA UK should be considered non-scalable and for illustrative purposes only. Issued design principals form instructions for the installation of DANOSA UK materials only and should be considered as part of an overall design rather than in isolation. Product 'Technical Datasheets' are available for all DANOSA UK products and should be consulted in conjunction with all issued DANOSA UK installation instructions. Drawings are subject to copyright and should not be reproduced without permission.

Cavity Tray / DPM  
(see Note E)

Lead Sealant or Chase Mortar  
(see Note C)

Mechanical Restraint  
(see Note D)

Lead Flashing

Minimum 50mm Cover  
(past mechanical penetration)

Minimum 150mm  
Upstand Height  
(see Note B)

DANOSA Capsheet  
(as specification)

DANOSA Underlay  
(as specification)

GLASDAN 800 PERFORADO  
(see Note A)

Angle Fillet

**Drawing Notes:**

All substrates should be primed or prepared in accordance with the project specification. Structural substrates shown in this drawing are for illustrative purposes only.

All reinforced bitumen membrane side overlaps should be a minimum of 80mm and head laps a minimum of 100mm.

Note A:  
Where a full bond to the substrate is required, or where ESTERDAN 30 P ELAST SEMIADHESVIO is used as the underlay, GLASDAN 800 PERFORADO does not form part of the system.

Note B:  
Minimum upstand height is measured from the finished surface of the roof finishes to the first mechanical penetration of the waterproofing or otherwise vulnerable junction. When specifying any finishes, such as paving slabs, stone ballast or a living roof, the measurement is made from the top surface of the finishes, not from the waterproofing level.

Note C:  
Sealants are considered maintenance items and should be checked and replaced regularly as part of annual roof maintenance procedures.

Note D:  
DANOSA Edge Restraint Bar (or similar), mechanically fastened at 200mm centres.

Note E:  
The cavity tray / DPM must discharge over the top of any lead counterflashing,



Building together

DANOSA UK Limited

Tel: 0845 074 0553 | www.danosa.co.uk | uktechnical@danosa.com

<b>Drawing Number:</b> DUK-B-(G)-321C	<b>Revision:</b> 01
<b>Date Drawn:</b> February 2019	<b>Author:</b> SL

**Drawing Title:**  
Abutment >250mm High with Lead Counterflashing  
Reinforced Bitumen Membranes - Cold Roof